



SAFETY DATA SHEET FOUNDATION SEALER

Supplier: Cantex Coatings Ltd.

Address: 722 Broad Street
Dunnville, ON N1A 1H1
Phone: 905-544-1501

**THIS PRODUCT IS NOT SUBJECT TO THE CONTROLLED PRODUCTS OR THE
TRANSPORTATION DANGEROUS GOODS REGULATIONS**

SECTION 1 – MATERIAL IDENTIFICATION

Trade Name	FOUNDATION SEALER
Chemical Family	Water suspension of petroleum derived hydrocarbons (polymer modified emulsified asphalt) and inert fillers
Material Use	Protective coating / Water proofing aid
T.D.G. Classification	NON REGULATED
WHIMIS Classification	NON REGULATED
Emergency Telephone	Canutec +01 613-996-6666

SECTION 2 – HAZARDOUS INGREDIENTS

COMPONENT:	CAS#	% (By Mass)	LC50 (ppm) (rat ihal)	LD50 (mg/kg) (rat oral)
ASPHALT	8052-42-4	40-70	n/a	n/a
Resin acids and Rosin acids, potassium salts	61790-50-9	1-5	n/a	n/a
Composition Comments	The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200			

SECTION 3 – PHYSICAL PROPERTIES

Colour	Brown
Appearance	Liquid
Physical State	Liquid
Odour	Slight asphalt
Specific gravity	1.0
Freezing Point	32° F (0° C)
Boiling Point	212° F (100° F)

Coefficient of water/oil distribution	Not available
Vapour pressure (mm/Hg)	To water
pH	Not available
Vapour density (air = 1)	Not available
Evaporation rate (nBuAcetate = 1)	< 1
Solubility in water	Not available

SECTION 4 – FIRE & EXPLOSION DATA

Suitable extinguishing media	Treat for surrounding material
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire
Specific hazards arising from the chemical	Firefighters should wear a self-contained breathing apparatus
Special protective equipment and precautions for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus
Fire-fighting equipment/instructions	Move containers from fire area if it can be done without risk
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials
General fire hazards	No unusual fire or explosions noted
Hazardous combustion products	May include and are not limited to : Oxides of sulfur and Oxides of carbon
Explosion Data	
Sensitivity to mechanical impact	Not expected to be sensitive to mechanical impact
Sensitivity to static discharge	Not expected to be sensitive to static discharge

SECTION 5 – REACTIVITY DATA

Chemical stability	Stable under recommended storage conditions
Incompatible materials	Oxidizers, Acids, Cautics
Hazardous decomposition products	May include and are not limited to: Oxides of carbon, Oxides of carbon
Hazardous polymerization	Will not occur

SECTION 6 – HEALTH INFORMATION

Exposure limit	
Ingestion	May cause stomach distress, nausea or vomiting
Inhalation	May cause respiratory tract irritation
Skin	Causes skin irritation
Eyes	Causes serious eye irritation
Chronic effects	

EMERGENCY AND FIRST AID PROCEDURES

Ingestion	Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur
Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention
Skin	If on skin: Wash with plenty of water. Specific treatment (see product label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Eyes	If in eyes: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention

SECTION 7 – SPILL PROCEDURES

Personal precautions, protective equipment and emergency procedures	Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection see Section 8 of the SDS
Methods and materials for containment and cleaning up	Stop leak if can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Never return spills to original containers for re-use. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basement or confined areas.
Environmental precautions	Do not discharge into lakes, streams, ponds or public waters
Waste disposal method	Follow Federal, Provincial and local regulations regarding disposal

SECTION 8 – SPECIAL PROTECTION

Respiratory protection	n/a
Ventilation	n/a
Protective gloves	Recommended
Eye protection	Safety glasses/splash goggles recommended
Other protective equipment	Long sleeves, loose clothing recommended

SECTION 9 – SPECIAL PRECAUTIONS

Storage and handling conditions	KEEP FROM FREEZING. Keep containers tightly closed when not in use.
Special shipping information	Not regulated by the Transportation of Dangerous Goods Regulations

Prepared by **Cantex Coatings Ltd.**

Preparation date 2021 November 23 Replaces 2020 November 13

The information contained herein is based on available data and is provided for information only. Cantex Coatings Ltd makes no warranties, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use thereof. Cantex Coatings Ltd will not be liable for any damages arising from the use of the information, or product described on this data sheet.